



Over Counter Dispenser



The Multiplex 'Over Counter' is a high-capacity dispenser with an eye-catching visual merchandiser.

Drawing on the proven performance, reliability, energy efficiency, features, and benefits of the Icecore range.

- High capacity in a compact design
- Highly visible merchandiser with illumination and video options
- 'Smart air flow' allowing installation in tight spaces and alongside other equipment.
- Universal compatibility with all post mix valves
- Common critical parts with the Icecore range

Standard features

- EC motor technology.
- Six products.
- Easy installation with front access to all connections.
- 2.5L drip tray with drain option.
- Generous service accessibility.
- Control options including programmable trading hours with smart recovery for trade readiness.
- 600mm depth (standard countertop depth).
- No requirement for rear or side air gaps
- Common parts with Icecore 10
- Up to 40% energy saving with programmable trading hours.
- 8kg Ice Bank with 120 drinks per hour continuously

In a world where energy saving, material waste and running costs are growing concerns this post mix dispenser uses natural refrigerants dramatically reducing energy consumption and lowering your carbon footprint.



ISO 9001: 2000
Quality System Certified



Specifications

PERFORMANCE - 24°C AMBIENT, DRINKS AT OR BELOW 4.4°C

Ice Bank pull down @ 24°C	200 minutes
Ice Bank weight	8 kg +/- 1 kg
*Dispense capacity	269 x 355ml @ 2DPM <4.4°C
Optimized ambient temperature	24°C
Max operating temperature	41°C

PHYSICAL DATA

Height	688mm
Width	480mm
Depth	600mm
Water bath capacity	25 Litres
Dry weight	66kg
Operating weight	91kg

ELECTRICAL

Mains voltage\ frequency	230V/50Hz
Run current	
Fuse rating	10 amps

WATER & CO₂ PRESSURE

Max\Min water pressure	50\20 psi
Max\Min CO ₂ pressure	75\90 psi

REFRIGERATION

Compressor type \ displacement	High efficiency 11cc
Duty @ -10°C evaporation	886W
Refrigerant	R290 (Propane)
Refrigerant charge	<150g

CARBONATION SYSTEM

Carbonator pump	455 Litre/hr
Carbonator pump motor	150W
Carbonator Bowl reserve	1.6 Litres

*/** ASSUMED OPERATING CONDITIONS:

Ambient operating temperature = 24°C Ambient, incoming water and syrup.



Options



BRONZE	SILVER (BRONZE+)	GOLD (SILVER+)	PLATINUM (GOLD+)
6 Back Blocks (no valves)	Valve Isolation Switch	3 x selectable carb/still	HD Video Screen
All carb or 1 x still + 5 carb (fixed)	Electronic Ice Bank Control	Branding illumination	
EC condenser fan and agitator	Programmable Trading Hours	Dispense area illumination	
Mechanical Ice Bank Control	Smart Recovery		
Branding Panel	Condenser Filter		
Silver Coated Outer Panels	Stainless Steel Outer Panels		
Moulded Fascia & Drip Tray			
Plumb to drain drip tray			

