

VISION V15^e (R-290) Hydrocarbon

Remote Cooler

Model

☐ V15 Integral



Standard Features

- The Vision remote cooler is engineered for the cellar environment and offers improvements in serviceability.
- The integral Vision cooler hosts a range of features and benefits.


Benefits

- Electronic ice bank control
- 18mtr lid mounted pump
- Front mounted condenser fan
- Improved IP rated electrical enclosure
- Three removable service panels (front and 2-sides)
- Improved ice bank stability
- Increased tank insulation
- Overall improved performance
- Telemetry electrical interface as standard

VISION V15e (R-290) Remote Cooler

Specifications

VISION 15 INTEGRAL

Performance		
Ice Bank Pull Down @ 19°C Ambient Waterbath		2:45
Ice Bank Weight		11 Kg (nominal)
Max Operating Ambient Temperature		32°
Physical Data		
	Height	770 mm
	Width	425 mm
	Depth	500 mm
	Waterbath	28 litres
	Dry Weight	43.5 Kg
	Operating Weight	61.5 Kg
Electrical		
Mains Voltage		230V
Run Current		5.0 amps
Fuse Rating		10 amps
Refrigeration		
Compressor Size		8.8cc
Duty @ -10°C Evaporation		689 watts*
Refrigerant		R290
Charge		105 g
Controls		
Ice Bank		Electronic
System Protection		
Compressor		Klixon (Auto reset)
Recirculation Pump		Thermal overload (Auto reset)
Coils		
Plain Lid		0 coils
Coil Lid		4 x 6m x 3/8" Coils (316 st/st)

* Compressor manufacture's data for compressor @ -10°C evaporation temperatures, according to EN 12900 Household (CECOMAF)

Head Office
Manitowoc Beverage Systems
Chancel Way, Halesowen
West Midlands, B62 8SE, UK

Tel: +44.121.501.2566
Fax: +44.121.500.0873
mbs.uk@manitowoc.com

www.manitowocbeverage.com

